

SPECIFICATION SHEET SF-N235

3/4 DIPPED NITRILE WITH NITRILE DOTS GOVES

Description

This 3/4 dipped micro-foam nitrile glove features nitrile dots on a 15 gauge nylon and elastane shell. The micro-foam nitrile coating with nitrile dots provides outstanding wet/oily grip plus wear and abrasion resistance.

- * Lightweight 15 gauge 40% nylon/60% elastane construction gives silky feel and offers fantastic dexterity and 360° breathability.
- * Ultra-thin and flexible micro-foam nitrile coating with nitrile dots ensures good abrasion performance and an outstanding grip in wet, dry and heavy oil applications and .
- * 3/4 dipped for increased protection.
- * Elastic cuffs offers a secure fit and protection from debris.



100% Nitrile Coating

Applications

- * Construction, Small-Parts Handling
- * General Industry, Maintenance
- * Automotive, Shipping/Receiving
- * Furniture Manufacturing, Assembly

Care Instructions

- * Wash in warm water (30-40°C) (86-104°F)
- * Use mild detergent
- * Short cycle time (5-10 minutes)
- * Low tumble dry (60°C max) (140°F max)



For more information please contact us at
www.superfitglove.com

1031 S Linwood Ave Santa Ana CA 92705
949.296.6290 | sales@superfitglove.com



SUPER FIT GLOVE



TECHNICAL DATA

Raw Material of Shell	40% Nylon/60% Elastane
Raw Material of Coating	100% Nitrile
Dip	3/4 Palm
Color	Grey Shell, Black Coating
Size	S-7, M-8, L-9, XL-10
Packaging	5 pairs per polybag, 20 polybags per case
Case Dimensions	9.5" high x 17" wide x 13" deep
Storage	Store dry and cool sheltered from direct sunlight
Country of Origin	China

4141 CE 

EN388 TEST RESULTS

Abrasion Resistance	LEVEL 4
Cut Resistance	LEVEL 1
Tear Resistance	LEVEL 4
Puncture Resistance	LEVEL 1