

flexstone™ MICRO-FOAM NITRILE COATED LEVEL A3 CUT RESISTANT GLOVES, REINFORCED AT THE THUMB AND INDEX FINGER - 13 GAUGE

Description

This lightweight soft, moisture-wicking and seamless glove delivers a unique combination of ANSI level A3 cut resistance and micro-foam nitrile coating.

- Lightweight soft, moisture-wicking and seamless construction offers increased comfort and 360° breathability.
- FlexStone™ shell provides excellent dexterity, tactile sensitivity, heat resistance and cut resistance.
- Meets EN407 :2004 Contact Heat Level 1, ANSI Level A3 Cut Resistance.
- Ultra-thin and flexible micro-foam nitrile coating allows for maximum breathability and ensures a secure grip in wet, dry and heavy oil applications.
- Reinforcement between the thumb and index finger, improves cut resistance and provides extra wear protection.
- Color coded hems for easy size identification.




Applications

- Handling Sharp Objects
- Metal Stamping, Metal Fabrication
- Automotive Industry, Construction
- Glass Plants, Aerospace Industry

Care Instructions

- Wash in warm water (30-40°C) (86-104°F)
- Use mild detergent
- Short cycle time (5-10 minutes)
- Low Tumble dry (60°C max) (140°F max)



Technical Data

SHELL	GAUGE	COLOR	DIP	COLOR	COATING	ANSI	EN388	EN407	COO
FLEXSTONE	13	SALT & PEPPER	1/2 PALM	BLACK	MICRO-FOAM NITRILE	A3	4X43D	Level 1	CHINA

Size & Packaging

	5 (XXS)	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)
CASE (120 PAIRS)	120 PAIRS	120 PAIRS	120 PAIRS	120 PAIRS	120 PAIRS	120 PAIRS
CASE WEIGHT(LB)	14.3	15.4	16.5	18.7	19.8	20.9
HEM COLOR	GREEN	PURPLE	RED	YELLOW	BROWN	BLACK

