

SPECIFICATION SHEET SF-NY291

PROTECTIVE NITRILE CONSTRUCTION GLOVES

Description

This protective nitrile construction glove is lightweight abrasion resistant and chemical resistant with open back for ventilation.

- * Cotton interlock fabric lining for comfort and dexterity.
- * The construction of the glove helps reduce hand fatigue and improve comfort and breathability.
- * Good grip and abrasion performance on wet and dry conditions.
- * Nitrile coated palms for chemical protection.
- * 3/4 dipped for increased protection.
- * Perfect for general handling and construction jobs.



100% Nitrile Coating

Applications

- * Construction, Small-Parts Handling
- * General Industry, Maintenance
- * Automotive, Shipping/Receiving
- * Furniture Manufacturing, Assembly

Care Instructions

- * Wash in warm water (30-40°C) (86-104°F)
- * Use mild detergent
- * Short cycle time (5-10 minutes)
- * Low tumble dry (60°C max) (140°F max)



For more information please contact us at
www.superfitglove.com

1031 S Linwood Ave Santa Ana CA 92705
949.296.6290 | sales@superfitglove.com



SUPER FIT GLOVE



TECHNICAL DATA

Raw Material of Shell	Cotton Interlock Fabric Lining with Knit Wrist
Raw Material of Coating	100% Nitrile
Dip	3/4 Palm
Color	Off White Shell, Yellow Coating
Size	L-9, XL-10
Packaging	12 pairs per polybag, 10 polybags per case
Case Dimensions	10" high x 21" wide x 10" deep
Storage	Store dry and cool sheltered from direct sunlight
Country of Origin	China

4111 CE 

EN388 TEST RESULTS

Abrasion Resistance	LEVEL 4
Cut Resistance	LEVEL 1
Tear Resistance	LEVEL 1
Puncture Resistance	LEVEL 1